AMENDMENTS TO THE CLAIMS

- At the time of the Action: Claims 15-39.
- Withdrawn Claims: Claims 1-14.
- Amended Claims: Claims 15, 21, and 26.
- After this Response: Claims 15-39.

The following listing of claims replaces all prior versions and listings of claims in the application.

- (Withdrawn) A method of combining formats for an electronic file, comprising:
 combining opaque binary data having at least two different encodings; and
 presenting the combined data as homogenized data according to a reference encoding,
 wherein the homogenized data comprises a single package without having to perform
 character set-to-character set encodings.
- 2. (Withdrawn) A method according to Claim 1, wherein the reference encoding includes at least one of the at least two different encodings.
- 3. (Withdrawn) A method according to Claim 2, wherein the reference encoding is XML.
- 4. (Withdrawn) A method according to Claim 3, wherein the combined data is encoded into a single XML information set.

- 5. (Withdrawn) A method according to Claim 1, wherein the combining comprises referring to data.
- 6. (Withdrawn) A method according to Claim 1, wherein the combining comprises interleaving data.
- 7. (Withdrawn) A method according to Claim 5, wherein the combining comprises referring to data using an include element to reference binary data.
- 8. (Withdrawn) A method according to Claim 7, wherein a href (Hypertext REFerence) attribute of the include element provides a universal resource identifier of the binary data to be referenced.
- 9. (Withdrawn) A method according to Claim 5, wherein the combined data is presented as a MIME serialization.
- 10. (Withdrawn) A method according to Claim 7, wherein the include element comprises a simple object access protocol (SOAP) header block.
- 11. (Withdrawn) A method according to Claim 10, wherein the SOAP header block indicates that the combined data includes the XML include element, and points to cached representations of media resources.

- 12. (Withdrawn) A method according to Claim 11, wherein the SOAP header block points to any one of a web resource, an audio resource, and an image resource.
- 13. (Withdrawn) A method according to Claim 6, wherein the combining comprises combining data fragments, each data fragment being defined by values corresponding to a respective encoding, length, and content.
- 14. (Withdrawn) A method according to Claim 13, wherein a data fragment is notated as <encoding> <length> <content>.
- 15. (Currently Amended) A computer-readable medium having computer executable instructions stored on a computing device including a data structure, comprising:

a first data field encoded according to a first format, wherein the first format is XML; and a second data field referring to data encoded according to a second format, wherein the second format is JPEG;

wherein the first data field and the second data field are homogenized according to a reference encoding format for presentation into a single electronic format;

wherein the homogenized comprises combining within a single package <u>data partially</u> encoded as XML and partially as opaque binary data without having to perform character set-to-character set encodings;

wherein the reference encoding format can be generalized to other formats; and wherein the reference encoding format can be split into parts.

- 16. (Original) A computer-readable medium according to Claim 15, wherein the reference encoding is XML.
- 17. (Original) A computer-readable medium according to Claim 15, wherein the homogenized data is encoded into a single XML information set.
- 18. (Original) A computer-readable medium according to Claim 15, wherein at least one of the first data field and the second data field comprises an include element to reference binary data.
- 19. (Original) A computer-readable medium according to Claim 15, wherein a href attribute of the include element provides a universal resource identifier of the binary data to be referenced.
- 20. (Original) A computer-readable medium according to Claim 15, wherein at least one of the first data field and the second data field comprises an include element to reference one of a web resource, an audio resource, and an image resource.

21. (Currently Amended) A computer-readable medium having computer executable instructions stored on a computing device including a data structure, comprising:

a first data fragment encoded according to a first format, wherein the first format is XML;

a second data fragment encoded according to a second data format, wherein the second format is JPEG;

wherein the first data field and the second data field are homogenized according to a reference encoding format for presentation into a single electronic format;

wherein the homogenized comprises combining within a single package <u>data partially</u> encoded as XML and partially as opaque binary data without having to perform character set-to-character set encodings;

wherein the reference encoding format can be generalized to other formats; and wherein the reference encoding format can be split into parts.

- 22. (Original) A computer-readable medium according to Claim 21, wherein the reference encoding is XML.
- 23. (Original) A computer-readable medium according to Claim 22, wherein the homogenized data is encoded into a single XML information set.
- 24. (Original) A computer-readable medium according to Claim 21, wherein both the first and the second data fragment are defined by values corresponding to a respective encoding, length, and content.

- 25. (Original) A computer-readable medium according to Claim 24, wherein both the first data fragment and the second data fragment are formatted as <encoding> <length> <content>.
- 26. (Currently Amended) A method of transmitting data to a receiving node, comprising:

combining data having at least two different encodings, wherein a first data encoding according to XML format and a second data encoding according to JPEG format;

homogenizing the combined data in accordance with a reference encoding, wherein the homogenizing comprises combining within a single package <u>data partially encoded as XML and partially as opaque binary data</u> without having to perform character set-to-character set encodings; and

transmitting homogenized data to the receiving node over a network; wherein the reference encoding format can be generalized to other formats; wherein the reference encoding format can be split into parts.

- 27. (Original) A method according to Claim 26, wherein the reference encoding includes at least one of the at least two different encodings.
- 28. (Original) A method according to Claim 27, wherein the reference encoding is XML.

- 29. (Original) A method according to Claim 28, wherein the combined data is homogenized into a single XML information set.
- 30. (Original) A method according to Claim 26, wherein the combining includes resolving to data.
- 31. (Original) A method according to Claim 26, wherein the combining includes interleaving data.
- 32. (Original) A method according to Claim 30, wherein the combining includes resolving to data using an include element to reference binary data.
- 33. (Original) A method according to Claim 32, wherein an attribute of the include element provides a universal resource identifier of the binary data to be resolved.
- 34. (Original) A method according to Claim 30, wherein the combined data is presented as a MIME serialization.
- 35. (Original) A method according to Claim 32, wherein the include element resolves to cached representations of media resources.
- 36. (Original) A method according to Claim 35, wherein the cached representations of media resources are cached separately from the include element.

- 37. (Original) A method according to Claim 35, wherein the include element resolves to any one of a web resource, an audio resource, and an image resource.
- 38. (Original) A method according to Claim 26, wherein the combining includes combining data fragments, each data fragment being defined by values corresponding to a respective encoding, length, and content.
- 39. (Original) A method according to Claim 26, wherein a data fragment is notated as <encoding> <length> <content>.